





Retarder Prover Room - AVANT


DATA SHEET

mm 2100x1810x2500h



External dimensions





OPTIONS Stainless steel AISI 304 18/10 Internal finishing External finishing Stainless steel AISI 304 18/10 Stainless steel AISI 304 18/10 inishing Phenolic multilayer wood thickness А 21mm + s/s ramps. В Insulated and reinforced floor, thickness of insulation 60mm with exposed phenolic multilayer wood + s/s ramp С Insulated and reinforced floor, thickness of insulation 60mm with anti-slip stainless steel AISI 304 18/10 finishing + s/s ramps. nsing unit n.1 Silenced and tropicalized with Tecumseh compressor of 4Hp + accessories - Volt 3x400+N, 50Hz distance 10m Double toughened glass mm 300x300

		interna interning	
Internal dimensions	mm 1880x1650x1980h	External finishin	
Maximum external height	mm 2970	External front fir	
Structure	Prefabricated modular panels with thickness of insulation 60mm. Polyurethane rigid foam without	Floor – Version	
	CFC and density 38/40 Kg/mc. Sanitary profiles on the floor and ceiling	Floor – Version	
Floor	Without floor	Floor – Version	
Internal finishing	White painted galvanized sheet		
External finishing	White painted galvanized sheet		
Doors – entry	n.2 mm 800x2000h – industrial closing	Remote conden	
Capacity of racks - trays	n.4 for trays mm 600x800		
Evaporator	n.1 with four fans Ø 250mm	Door Glass	
Evaporator capacity	4970 Watt a 2°C room / -8°C evaporation		
Fans absorption	260 Watt		
Tropicalized condensing unit	n.1 ermetic Tecumseh compresor of 3Hp with n.2 fans. Dimensions mm 910x630x400h. Pump Down. High and low pressure switch		
Condensing unit capacity	5021 Watt at -10°C evaporation / 38°C condensation		
Defrosting resistances	n.1 of 1800 Watt		
Heating elements	n.2 of 2500 Watt		
Steam generator	n.2 of 1000W S/S - non-water contact resistance		
Temperature range	-5 / +40 °C		
Humidity range	50 – 100 %		
Temperature probe	n.1 Ntc		
Humidity probe	n.1 4-20mA		
Internal light	n.1 led of mm500		
Avant controller	n.1 Digital with LCD display and 4 programming keys		
Voltage	Volt 3x400+N 50Hz		
Gas	R452a		
Maximum absorption	7,7 Kw.		

С	O	D	E

AV80-2P-210x181