


Retarder Prover Room - AVANT



DATA SHEET

External dimensions	mm 2400x2310x2500h
Internal dimensions	mm 2180x2090x1980h
Maximum external height	mm 3050
Structure	Prefabricated modular panels with thickness of insulation 60mm. Polyurethane rigid foam without CFC and density 38/40 Kg/mc. Sanitary profiles on the floor and ceiling
Floor	Without floor
Internal finishing	White painted galvanized sheet
External finishing	White painted galvanized sheet
Doors – entry	n.2 mm1000x2000h – industrial closing
Capacity of racks - trays	n.4 for trays mm 800x1000
Evaporator	n.2 with three fans Ø 250mm
Evaporator capacity	7700 Watt a 2°C room / -8°C evaporation
Fans absorption	390 Watt
Tropicalized condensing unit	n.1 ermetic Tecumseh compressor of 5Hp with n.2 fans. Dimensions mm 1020x700x554h. Pump Down. High and low pressure switch
Condensing unit capacity	7384 Watt at -10°C evaporation / 38°C condensation
Defrosting resistances	n.2 of 1300 Watt
Heating elements	n.4 da 1800 Watt
Steam generator	n.4 of 1000W S/S - non-water contact resistance
Temperature range	-5 / +40 °C
Humidity range	50 – 100 %
Temperature probe	n.1 Ntc
Humidity probe	n.1 4-20mA
Internal light	n.2 leds of mm500
Avant controller	n.1 Digital with LCD display and 4 programming keys
Voltage	Volt 3x400+N 50Hz
Gas	R452a
Maximum absorption	12 Kw.

OPTIONS

Internal finishing	Stainless steel AISI 304 18/10
External finishing	Stainless steel AISI 304 18/10
External front finishing	Stainless steel AISI 304 18/10
Floor – Version A	Phenolic multilayer wood thickness 21mm + s/s ramp
Floor – Version B	Insulated and reinforced floor, thickness of insulation 60mm with exposed phenolic multilayer wood + s/s ramp
Floor – Version C	Insulated and reinforced floor, thickness of insulation 60mm with anti-slip stainless steel AISI 304 18/10 finishing + s/s ramp
Remote condensing unit	n.1 Silenced and tropicalized with Tecumseh compressor of 6Hp + accessories – Volt 3x400+N, 50Hz – distance 10m
Door Glass	Double toughened glass mm 300x300

CODE

AV100-2P-240x231